

# Sprinter UPS Block Battery Selection Guide

UPS Top Terminal Valve Regulated Lead Acid (VRLA) Block Batteries

Note: Power Battery version PRC is non-flame retardant; Delete "F" suffix to specify NON-Flame Retardant Sprinter

February 2011



Company	MODEL	Volts	WATTS PER CELL**	Size - L x W x H (inches)	Weight (lbs)
<b>GNB-Exide</b>	<b>S12V120F</b>	<b>12</b>	<b>117</b>	<b>6.82 x 6.58 x 5.89</b>	<b>27</b>
replaces Power	PRC or TC-1225	12	73	6.50 x 6.81 x 4.94	21.5
replaces Power	PRC or TC-1225X	12	71	6.50 x 6.81 x 4.94	21.5
replaces Power	PRC or TC-1230X	12	97	7.71 x 5.18 x 7.19	25.8
replaces Power	PRC or TC-1235L	12	118	7.71 x 5.18 x 7.19	26.7
replaces Power	PRC or TC-1235X	12	118	7.71 x 5.18 x 7.19	26.7

Company	MODEL	Volts	WATTS PER CELL**	Size - L x W x H (inches)	Weight (lbs)
<b>GNB-Exide</b>	<b>S12V170F</b>	<b>12</b>	<b>167</b>	<b>7.81 x 6.58 x 7.01</b>	<b>36</b>
replaces Power	PRC or TC-1250XL	12	183	8.61 x 5.29 x 8.79	35.3
replaces Power	PRC or TC-1255S	12	183	9.00 x 5.50 x 9.00	37

Company	MODEL	Volts	WATTS PER CELL**	Size - L x W x H (inches)	Weight (lbs)
<b>GNB-Exide</b>	<b>S12V285F</b>	<b>12</b>	<b>285</b>	<b>10.25 x 6.85 x 8.80</b>	<b>61</b>
replaces Power	PRC or TC-1265	12	185	10.20 x 6.67 x 9.66	50.7
replaces Power	PRC or TC-1265S	12	184	10.20 x 6.67 x 8.85	50.7
replaces Power	PRC or TC-1280X	12	223	10.20 x 6.67 x 9.66	58
replaces Power	PRC or TC-1290S	12	283	10.20 x 6.67 x 8.85	60.6
replaces Power	PRC or TC-1290X	12	283	10.20 x 6.67 x 9.66	60.6
replaces Power	PRC or TC 1290S	12	283	10.20 x 6.67 x 8.85	60.6

Company	MODEL	Volts	WATTS PER CELL**	Size - L x W x H (inches)	Weight (lbs)
<b>GNB-Exide</b>	<b>S12V300F</b>	<b>12</b>	<b>306</b>	<b>10.25 x 6.85 x 8.80</b>	<b>63</b>
replaces Power	PRC or TC-12100S	12	318	12.00 x 6.68 x 8.85	71.9
replaces Power	PRC or TC-12100X	12	318	12.00 x 6.68 x 9.71	71.9
replaces Power	PRC or TC-12100S	12	318	12.00 x 6.68 x 8.85	71.9

Company	MODEL	Volts	WATTS PER CELL**	Size - L x W x H (inches)	Weight (lbs)
<b>GNB-Exide</b>	<b>S12V370F</b>	<b>12</b>	<b>373</b>	<b>12.05 x 6.85 x 8.80</b>	<b>74</b>
replaces Power	PRC or TC-12110X	12	326	13.54 x 6.76 x 9.78	78.7
replaces Power	PRC or TC-12110XC	12	326	13.54 x 6.76 x 9.02	77.8
replaces Power	PRC or TC-12120X	12	371	13.54 x 6.76 x 9.78	81.8
replaces Power	PRC or TC-12120XC	12	371	13.54 x 6.76 x 11.02	80.8
replaces Power	PRC or TC-12120S	12	371	13.50 x 6.76 x 9.25	81.8

Company	MODEL	Volts	WATTS PER CELL**	Size - L x W x H (inches)	Weight (lbs)
<b>GNB-Exide</b>	<b>S12V500F</b>	<b>12</b>	<b>505</b>	<b>13.55 x 6.76 x 10.90</b>	<b>106</b>
replaces Power	PRC or TC-12150X	12	452	13.54 x 6.76 x 11.79	100.1
replaces Power	PRC or TC-12150XC	12	452	13.54 x 6.76 x 11.02	99.4
replaces Power	PRC or TC-12150C	12	505	13.50 x 6.76 x 10.87	100.1
replaces Power	PRC or TC-12160C	12	582	13.50 x 6.76 x 11.80	100.1

Company	MODEL	Volts	WATTS PER CELL**	Size - L x W x H (inches)	Weight (lbs)
<b>GNB-Exide</b>	<b>S6V740F</b>	<b>6</b>	<b>746</b>	<b>12.05 x 6.85 x 8.80</b>	<b>74</b>
replaces Power	PRC or TC-6165X	6	505	10.62 x 7.28 x 11.60	68.8
replaces Power	PRC or TC-6165XC	6	505	10.62 x 7.28 x 10.93	68
replaces Power	PRC or TC-6200X	6	618	10.62 x 7.28 x 11.60	77.2
replaces Power	PRC or TC-6200XC	6	552	10.62 x 7.28 x 10.93	76.3
replaces Power	PRC or TC-6200S	6	618	10.70 x 7.38 x 11.60	77.2
replaces Power	PRC or TC-6225X	6	686	10.62 x 7.28 x 11.60	82.2
replaces Power	PRC or TC-6225XC	6	686	10.62 x 7.28 x 10.93	81.5
replaces Power	PRC or TC-6225S	6	686	10.70 x 7.38 x 11.60	82.2

\*\* WATTS PER CELL @  
15 MIN. RATE TO 1.67 VPC @ 25°C



**High Rate Performance**